AEO | PRODUCT SPECIFICATIONS

AEO-8S5108-POE

Industrial 8-port Fast Ethernet PoE switch

English · Revision EN-20261101-V177

Backplane bandwidth	1.8Gbps
Packet buffer	1Mbits
MAC address table	2K
Maximum frame size (bytes)	2048bytes
Ethernet uplink ports	1 x 10/100Base-T(X) auto-negotiating Ethernet port
Network ports	8 x 10/100Base-T(X) auto-negotiating PoE Ethernet ports
Ethernet port characteristics	Half duplex, full duplex and auto-negotiation
Power input	44–57 VDC
Power consumption	≤5W (excluding PoE)
Power connector type	3 pin terminal block and Φ2.1mm DC connector
Reverse polarity protection	Supported
Power overload protection	Supported
Power redundancy	Supported
PoE	IEEE802.3af/at
PoE pin assignment	V+ V+ V- V- on pins 1, 2, 3, 6 (pins 4, 5, 7, 8 optional)
PoE output per port	IEEE802.3af：15.5W； IEEE802.3at：25.5W
IPC extension	Supported; up to 250m
One-touch VLAN	Supported
CBIT video optimization	Supported
EN61000-4-2 electrostatic discharge	±8KV contact discharge; ±15KV air discharge
EN61000-4-3 radiated immunity	10V/m(80～1000MHz)

EN61000-4-4 electrical fast transients	±10KV power line; ±2KV data line
EN61000-4-5 surge immunity	±10KV/CM, ±10KV/DM power line; ±2KV data line
EN61000-4-6 conducted immunity	3V(10KHz～150KHz)，10V(150KHz～80KHz)
Enclosure material	Aluminum alloy; fanless
Dimensions (L x W x H)	135 × 110 × 50mm
Mounting	35mm DIN rail
Operating temperature	-40 °C ~ 85 °C
Operating humidity	5% ~ 95% (non-condensing)
Protection rating	IP40

Product page: https://www.aeo-cctv.com/en/products_3/AEO_8S5108_POE
www.aeo-cctv.com/en/